

## IN THE SPECIFICATION

Please replace the following paragraphs with the amended paragraphs as noted:

[0004] Such a terminal connection is known in several embodiments from EP 0 528 233 B1 and has proven to be effective. Above all, this known terminal connection, indicated as 22 in Figures 9 and 10, is well suited for mounting, e.g., a cable 4 on a through-opening of a housing, and includes a threaded sleeve 23 and a counter-sleeve or nut 24 which can be threaded together so that the inside of the nut 24 presses inwardly on a terminal insert 25, wherein the contact of the terminal insert 25 on the cable 4 is realized only when the terminal connection 22 is mounted in the through-opening of the housing and the cable has been inserted.

[0030] Figure 7 is a view corresponding to Figures 5 and 6 for an approximately rectangular or quadratic collar, which is rotated for coupling with the coupling piece by 45°, ~~and also~~

[0031] Figure 8 is a view of a collar with two flattened sections and arc-shaped projections arranged between these sections, which fit into a corresponding recess of the coupling piece and are rotated for coupling by approximately 90°[.].

Please add the following new paragraphs after paragraph [0031]:

[0031.1] Figure 9 is a view, partially in cross-section, corresponding to the prior art connection of EP 0 528 233 B1, shown in a disassembled state, and

[0031.2] Figure 10 is a view, partially in cross-section, corresponding to the prior art connection of EP 0 528 233 B1, shown in an assembled state clamped to a cable.